



## GENERAL

Name	Amelie
Type	Handysize Seahorse
Built	February 2013
Flag	Liberia
Class	American Bureau of Shipping
DWAT	34.690 mts on 10,10 m (summer)
TPC	50,81 mt/cm (summer)
Tonnage	24.187 (GT) / 11.602 (NT)
LOA	180,00 m
Beam	30,00 m
Depth	14,70 m

## HOLDS & HATCHES

Hatchcover type	End folding steel hatchcover, hydraulically operated, double-skin construction					
Tanktop strength	22 mt/sqm					
		<b>Length</b>	<b>Breadth (fore/aft)</b>	<b>Height</b>	<b>Grain (cbm)</b>	<b>Bale (cbm)</b>
Hatchcovers	No.1	16,00 m	18,70 m / 15,00 m			
	No.2	19,20 m	20,30 m			
	No.3	19,20 m	20,30 m			
	No.4	19,20 m	20,30 m			
	No.5	19,20 m	20,30 m			
Cargo holds	No.1	27,40 m	26,00 m	15,10 m	7.648,00	7.818,00
	No.2	26,30 m	26,60 m	15,50 m	9.790,00	9.525,00
	No.3	26,20 m	26,60 m	15,50 m	9.782,00	9.525,00
	No.4	26,20 m	26,60 m	15,50 m	9.782,00	9.525,00
	No.5	26,30 m	26,60 m	15,10 m	9.428,00	9.276,00
<b>Total Capacity</b>					<b>46.730,00</b>	<b>45.669,00</b>

## GEAR & ENGINE

Crane type	Electro-hydraulic cranes
SWL	4 x 30 mt each
Outreach	Max. 26,20 m / Min. 4,00 m
Grabs type	No
Capacity	N/A
Main Engine type	Wartsila 5RT - flex 50D
Output	6350 KW
Aux. Engine type	MAN B&W 5L 23/30 H, 720 RPM
Output	3 x 600 KW

## OTHER FITTINGS

Logs fitted	No
Cement holes	4 x 790 mm diameter per each hold
Ventilation	Natural
Grain fitted	Yes
CO2 fitted	Yes
A60 bulkhead	Yes
Australian hold ladder	Yes
Strengthened for heavy cargo	No special strengthened

